



Materials: Aluminum Bronze

Tolerances: Thickness: +/- .001; Hole Position: +/- .005; All Other: +/- .010

Graphite	Grease Groove	T	W	L	A	B	C	E	F	G
SMC2602	PRE2602	.75	4.00	2.00	1.00			1.00		3.00
SMC2603	PRE2603			3.00	1.50			1.00		3.00
SMC2604	PRE2604			4.00	1.00		3.00		2.00	
SMC2605	PRE2605			5.00	1.00		4.00		2.00	
SMC2606	PRE2606			6.00	1.00		5.00		2.00	
SMC2608	PRE2608			8.00	1.00	4.00	7.00		2.00	
SMC2610	PRE2610			10.00	2.00		8.00	1.00		3.00
SMC2612	PRE2612			12.00	2.00		10.00	1.00		3.00
SMC2802	PRE2802	1.00	4.00	2.00	1.00			1.00		3.00
SMC2803	PRE2803			3.00	1.50			1.00		3.00
SMC2804	PRE2804			4.00	1.00		3.00		2.00	
SMC2805	PRE2805			5.00	1.00		4.00		2.00	
SMC2806	PRE2806			6.00	1.00		5.00		2.00	
SMC2808	PRE2808			8.00	1.00	4.00	7.00		2.00	
SMC2810	PRE2810			10.00	2.00		8.00	1.00		3.00
SMC2812	PRE2812			12.00	2.00		10.00	1.00		3.00

Ordering Note: Add "P" suffix for Drill and C'bore for 3/8 SHCS.