



Hole & OD Groove omitted on graphited bushings; depth of OD Groove: .03

With Graphite Plugs

L	Nominal I.D.							
	3/4	7/8	1	1 1/4	1 1/2	2	2 1/2	3
0.875	MS750-7							
1.250		MS875-10	MS100-10	MS125-10	MS150-10	MS200-10		
1.375	MS750-11	MS875-11	MS100-11	MS125-11	MS150-11			
1.500	MS750-12	MS875-12	MS100-12	MS125-12	MS150-12	MS200-12	MS250-12	
1.750			MS100-14	MS125-14	MS150-14			
1.875				MS125-15	MS150-15			
2.000			MS100-16	MS125-16	MS150-16	MS200-16	MS250-16	MS300-16
2.500						MS200-20		MS300-20
3.000			MS100-24	MS125-24	MS150-24	MS200-24	MS250-24	MS300-24
3.500								MS300-28
3.875						MS200-31		
4.875							MS250-39	MS300-39
D	0.7505	0.8755	1.0005	1.2505	1.5005	2.0005	2.5005	3.0005
A	1.1255	1.2505	1.3755	1.6255	2.0005	2.5005	3.2505	3.7505

With Grease Grooves

L	Nominal I.D.								L2
	3/4	7/8	1	1 1/4	1 1/2	2	2 1/2	3	
0.875	MS750-7P	MS875-7P							
1.250		MS875-10P	MS100-10P	MS125-10P	MS150-10P	MS200-10P			0.56
1.375	MS750-11P	MS875-11P	MS100-11P	MS125-11P	MS150-11P				0.56
1.500	MS750-12P	MS875-12P	MS100-12P	MS125-12P	MS150-12P	MS200-12P	MS250-12P		0.56
1.750			MS100-14P	MS125-14P	MS150-14P				0.56
1.875				MS125-15P	MS150-15P				0.56
2.000			MS100-16P	MS125-16P	MS150-16P	MS200-16P	MS250-16P	MS300-16P	0.56
2.500								MS300-20P	1.56
3.000			MS100-24P	MS125-24P	MS150-24P	MS200-24P	MS250-24P	MS300-24P	1.56
3.500								MS300-28P	1.56
3.875						MS200-31P			1.56
4.875							MS250-39P	MS300-39P	1.56
D	0.7505	0.8755	1.0005	1.2505	1.5005	2.0005	2.5005	3.0005	
A	1.1255	1.2505	1.3755	1.6255	2.0005	2.5005	3.2505	3.7505	

Materials: Aluminum Bronze

Tolerances: D, A: +.0005/-0.0000; L: +0/-0.06