



Materials: 1.2344 (H-13)

Hardness: Core: 50-52 Rc; Surface: 65-70 Rc

Prefix	D	H	T	Available Lengths					
	+0/-0.0003	+0/-0.010	+0/-0.002	4	6	8	10	12	14
EPH3-	1/32	1/8	1/8	.	.				
EPH4-	3/64	5/32	1/8	.	.				
EPH5-	1/16	3/16	1/8		
EPH6-	5/64	13/64	1/8		
EPH7-	3/32	7/32	1/8		
EPH8-	7/64	15/64	1/8		
EPH9-	1/8	1/4	1/8
EPH10-	9/64	1/4	1/8
EPH11-	5/32	9/32	5/32
EPH12-	11/64	11/32	3/16
EPH13-	3/16	3/8	3/16
EPH14-	13/64	3/8	3/16
EPH15-	7/32	13/32	3/16
EPH16-	15/64	13/32	3/16
EPH17-	1/4	7/16	3/16
EPH18-	17/64	7/16	1/4
EPH19-	9/32	7/16	1/4
EPH20-	19/64	1/2	1/4
EPH21-	5/16	1/2	1/4
EPH22-	21/64	9/16	1/4
EPH23-	11/32	9/16	1/4
EPH24-	23/64	5/8	1/4
EPH25-	3/8	5/8	1/4
EPH26-	25/64	37/64	1/4
EPH27-	13/32	11/16	1/4
EPH28-	27/64	11/16	1/4
EPH29-	7/16	11/16	1/4
EPH30-	29/64	45/64	1/4
EPH31-	15/32	3/4	1/4
EPH32-	31/64	3/4	1/4
EPH33-	1/2	3/4	1/4
EPH34-	17/32	25/32	1/4
EPH35-	9/16	13/16	1/4
EPH37-	5/8	7/8	1/4
EPH39-	11/16	15/16	1/4
EPH41-	3/4	1	1/4
EPH45-	7/8	1 1/8	1/4
EPH47-	1	1 1/4	1/4

Ordering Note: Catalog number is prefix plus length (e.g., EPH25-6).